Thinking of you
Electrolux

PROFESSIONAL LAUNDRY

Electrolux Dryers for Coin/Card Laundries

30x30 stack, 45x45 stack, 35, 67, and 83 lb.

High performance and significant energy savings.

Built to last, Electrolux dryers are precision-engineered for efficiency, ease of use, and superior drying results. Perfect for coin/card laundries, your customers will love the fast drying and user-friendly controls. You'll appreciate the "green" engineering, easy operation, and years of low maintenance.

Features and benefits:

- **EcoPower technology** saves you up to an additional 15% (or more) on energy costs. This energy-saving feature senses when laundry is dry and automatically reduces the operating temperature in the dryer. Gentler on clothing, less wrinkling, and lower energy consumption.
- **Reversing drums are standard!** With reversing, garments don't tangle therefore they dry more quickly using less energy.
- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption.
- Quiet operation. Designed to keep noise level below 70 dB (A).
- Sturdy drum suspension with double-sealed bearings and belt drive.
- Extra large doors make loading and unloading easy.
- Easy access to all parts.

Single Pocket Dryer features:

- **Axial airflow** and tight construction for extremely low energy consumption
- **Compass Pro** program control
- Top Exhaust Kit (optional)

GREEN RANGE

Energy saving

30x30, 45x45, 35, 67 and 83 lb. capacities.
Available in stainless or wave front panel.
Choice of card ready or drop coin payment.

The future of professional laundry is here.

Electrolux is dedicated to providing you with the very best precision-engineered washers, dryers, and flatwork ironers. Production units are certified in accordance with ISO 9001 (Quality) and ISO 14001 (Environmental Management) standards, and products are CE labeled. Take control of your laundry operations with Electrolux Professional Laundry.

For more information, please visit www.laundrylux.com

Electrolux Dryer Models	T4300		T4420S		T5290		T5550		T5675	
Capacity (lb/kg)	2 x 30	2 x 13.5	2 x 45	2 x 20.41	35	16.1	67	30.5	83	37.5
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960
Depth - Gas Models (in/mm)	43 11/16	1110	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810
Cylinder volume (ft^3/l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675
Crated Weight (lb/kg)	693	315	865	392	518	235	717	325	827	375
Utility Connections			(2) 8" or (1) 10"							
Exhaust duct diameter (in/mm)	8	200	(2) 203mm or (1) 254mm		8	200	10	250	10	250
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		1/2 NPT	
Energy Data										
Gas (Btu/hr)	2 x 71,700		2 X 94,000		71,700		112,700		143,400	
Airflow (ft^3 /min / m^3/hr) (gas heat)	2 x 354	2 x 600	2 x 600	2 x 1020	360 / 610		550 / 940		670 / 1140	
Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32	
Airflow (ft^3/min / m^3/hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140	
Electrical Requirements										
Current, gas, 120 V/60Hz (full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)	
Current, gas, 220-240 V/60Hz/1Ø (full load/circuit breaker)	2 x 4.5A / 2 x 15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)	
Current, gas, 208-240 V/60Hz/3Ø (full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2 x 50 / 2 x 65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)	
Alternate Voltages										
Alternate voltages available. Contact Laundrylux Sales Department for information.										
Supply Pressures										
Natural Gas (inches H_20/mbar)	6 - 10	15 - 25	6 - 12	15 - 30	3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26	
Propane (inches H_20/mbar)	10 - 13	25 - 30	11 - 13	28 - 33	8-13	20-32	8-13	20-32	8-13	20-32
Exhaust back pressure (inches H_20/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5

Note: T4420S 45 lb. stack dryer - 208 volt, 1-phase not available. Use 120 volt model for 208 volt applications.

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

ELECTROLUX DRYER CONTROLS

Compass PRO available on single pocket Electrolux dryers • Selecta II on 30x30 Stack and 45x45 Stack dryers.

Compass Pro - large and clear display, easy to use

- Easy program selection
- Easy access with user-friendly interface
- Language selection
- Service program for adjustment of parameters
- USB Type B connection

Call today for more information on Electrolux Professional washers and dryers. Be sure to ask about special financing.

Electrolux

800.381.7222 • www.laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com
Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com
Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com
En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer

#096245 2.08.12